

LASER[®]

Part No. 9480

Emergency Work Lamp & Power Bank Instructions



www.lasertools.co.uk

Introduction

A high-performance, multi-function LED work lamp featuring an integrated amber emergency warning light. The unit is equipped with two durable rubber suction pads for temporary mounting on smooth, flat surfaces, along with eight internal magnets to ensure secure attachment to ferrous materials. A combined carry and hanging handle is also incorporated for flexible positioning. Suitable for under-bonnet applications, vehicle roof or body mounting, and a wide range of indoor and outdoor environments, including roadside and low-light working conditions. Amber warning light ideal for roadside warning.

The lamp offers five selectable lighting modes: high-output white light (700 lumens), low-output white light (210 lumens), and three amber flashing modes (48 lumens). It utilises a total of 144 surface-mounted LEDs, comprising 96 forward-facing and 48 side-mounted units for broad area illumination. Power is supplied by two integrated 3.7V 2400mAh lithium-ion batteries, rechargeable via the included USB-C charging cable. The unit features a Type-C input port for charging and a Type-B output port providing 5W power bank functionality. Compliant with CE and RoHS standards.

Components



Ref.	Description
A	LED work lamp (white)
B	LED emergency light (amber)
C	Rubber suctions pads
D	USB-C charging cable
E	ON/OFF & control button Type-C input port (charging)
F	Type-C input port (charging)
G	Type-B USB (5W)
H	Brightness indicator panel
I	Combined carry & hanging handle

Instructions

Operation:

Press the ON/OFF & control button **(E)** repeatedly to cycle through the available lighting modes in the following order:

1. Work lamp high-output white light – 700 lumens
2. Work lamp low-output white light – 210 lumens
3. Amber flashing mode 1
4. Amber flashing mode 2
5. Amber flashing mode 3
6. Off

The work lamp can be mounted by the two suction cups **(C)**, on a ferrous metal surface by the eight internal magnets, or hung in a secure position by the combined carry and hanging handle **(I)**.

Specifications:

Dimensions:	255 x 140 x 65mm
Weight:	675g
Materials:	ABS & PC (polycarbonate)
Rechargeable batteries:	2 x 3.7V 2400mAh lithium-ion
Light source:	Work light: 96 x LED; Flashing amber: 48 x LED
Charging time:	3 hours
Output duration:	High-output white: 130 min; Low output white: 5.5 hrs; Flashing mode 1: 6 hrs; Flashing mode 2: 6 hrs; Flashing mode 3: 8 hrs.

Precautions



- Always read and understand these instructions before use.
- Ensure the work lamp is fully charged before first use.
- Do not switch the work lamp on while it is being charged.
- Position the work lamp on a flat, solid surface, or hung by the hanger in a secure position.
- Do not shine directly into your own, another person's, or an animal's eyes.
- Do not use the work lamp if the lamp casing, polycarbonate cover or battery is damaged.
- When charging via the USB Type-C port, ensure the USB power source is rated at 5V/1A.
- Do not leave the battery in a discharged state. Recharge battery immediately.
- When not in use, fully charge the work lamp, then store in a dry, clean and safe place away from the reach of children. Subsequently recharge the battery every three months of non-use.
- Keep the work lamp clean, wipe with a clean cloth. Do not let water enter the unit.
- Do not clean with solvents, petrol, etc.
- Do not attempt to open or dismantle the battery packs.
- Do not expose the work lamp to temperatures above 40°C or below -10°C.
- Do not expose to direct sunlight for long periods of time.
- Dispose of this product at the end of its service life in accordance with the EU Waste Electrical and Electronic Equipment (WEEE) Directive. When no longer required, the product must be disposed of in an environmentally responsible manner. For guidance on recycling and approved disposal facilities, contact your local waste authority.
- No liability is accepted for incorrect use of this product — do not use the product for tasks it is not designed for. Use the product correctly and with care. Failure to do so may cause damage and/or personal injury and will invalidate the warranty.



Safety First. Be Protected.

Our products are designed to be used correctly and with care for the purpose for which they are intended. No liability is accepted by the Tool Connection for incorrect use of any of our products, and the Tool Connection cannot be held responsible for any damage to personnel, property or equipment when using the tools. Incorrect use will also invalidate the warranty.

If applicable, the applications database and any instructional information provided has been designed to offer general guidance for a particular tool's use and while all attention is given to the accuracy of the data no project should be attempted without referring first to the manufacturer's technical documentation (workshop or instruction manual) or the use of a recognised authority such as Autodata.

It is our policy to continually improve our products and thus we reserve the right to alter specifications and components without prior notice. It is the responsibility of the user to ensure the suitability of the tools and information prior to their use.



When you have finished with
this bottle please recycle it

www.lasertools.co.uk



For GPSR regulations visit: www.tc-gpsr.com

Distributed by The Tool Connection Ltd

Kineton Road, Southam, Warwickshire CV47 0DR
T +44 (0) 1926 815000 F +44 (0) 1926 815888
info@toolconnection.co.uk www.toolconnection.co.uk

Guarantee

If this product fails through faulty materials or workmanship, contact our service department direct on: **+44 (0) 1926 818186**. Normal wear and tear are excluded as are consumable items and abuse.

9480_Instructions_V1

www.lasertools.co.uk