



INDUSTRIAL INFRARED DIESEL HEATERS

MODEL NO: IR13.V3, IR16.V3, IR19.V2, IR29

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.


IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instructions



Wear protective gloves



Always unplug before servicing and checking



Warning: Hot surfaces



Do not cover



Keep in dry area protect from rain



Use in well ventilated areas



Indoor use only

1. SAFETY

1.1. ELECTRICAL SAFETY

- ☐ **WARNING!** It is the user's responsibility to check the following:
 - ✓ Check all electrical equipment and appliances to ensure that they are safe before using.
 - ✓ Inspect power supply leads, plugs and all electrical connections for wear and damage.
 - ✓ If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified person in order to avoid a hazard.
 - ✓ Ensure that the insulation on all cables and on the appliance is safe before connecting it to the power supply.
 - ✗ **DO NOT** use worn or damaged cables, plugs or connectors.
 - ✓ Ensure that any faulty item is repaired or replaced immediately by a Sealey qualified technician.
 - ✓ If the cable or plug is damaged during use, switch off the electricity supply and remove from use.
 - ✓ Sealey recommend that an RCD (Residual Current Device) is used with all electrical products.
- ☐ **IMPORTANT:** Ensure that the voltage rating on the appliance suits the mains power supply.
- ✗ **DO NOT** pull or carry the appliance by the power cable.
- ✗ **DO NOT** pull the plug from the socket by the cable.
- ☐ **Ensure that repairs are carried out by a qualified electrician.**
- ☐ **GENERAL SAFETY**
- ☐ **WARNING! THIS HEATER IS FOR PROFESSIONAL USE. IT HAS BEEN CAREFULLY DESIGNED FOR MOBILE AND TEMPORARY PROFESSIONAL APPLICATIONS. IT HAS NOT BEEN DESIGNED FOR DOMESTIC USE NOR FOR COMFORT HEATING AND SHOULD NEVER BE USED TO HEAT CLOSED ROOMS WITHOUT ADEQUATE VENTILATION.**
- ▲ **DANGER!** Risk of carbon monoxide poisoning. Failure to provide proper ventilation could result in serious illness or death.
- ✓ Check that the heater is in sound condition and good working order. Take immediate action to repair or replace damaged parts.
- ✓ Use recommended parts only. Unauthorised parts may be dangerous and will invalidate the warranty.
- ✓ Only use diesel or kerosene to fuel this heater, in accordance with instructions contained in this manual.
- ✓ Locate heater on a level and stable surface.
- ☐ **WARNING!** Only use heater in well ventilated areas. Ensure continuous ventilation is provided to the heater operating area via windows and doors etc. If people are not required to be present in the heated area, the volume of air to be heated (m³)/heat output (kW) ratio must be at least 10:1 and people must be advised not to remain in the heated area for prolonged periods. If people are required to be present in the heated area, the volume of air to be heated (m³)/heat output (kW) ratio must be at least 30:1. Ventilation must be to the outside of the premises in which the heater is to be operated. The total open area (m²) must be at least 0.003 times the total heat output (kW). The volume concentration of oxygen (O₂) in the heated room, must always remain above 17%.
- ☐ **WARNING! DO NOT** use the heater near flammable material, liquids, solids, gases or compressed gas cylinders etc.
- ☐ **WARNING!** Consult the appliance manufacturer before replacing parts other than those specified or recommended in the servicing instructions.
- ✗ **DO NOT** stand or place any object less than 3m from the heater output and keep the heater a minimum of 2m from any walls or objects.
- ☐ **WARNING!** When assembling, installing, or maintaining, always ensure the unit is completely powered off and cooled down before handling. Wear appropriate personal protective equipment (PPE), such as gloves and eye protection, to prevent burns or injury. Use only manufacturer-approved parts and follow all assembly instructions carefully to avoid gas or fuel leaks. During installation, verify that the location is properly ventilated and free of flammable materials. Ensure that all fuel lines and electrical connections are secure and leak-free. During maintenance, routinely check for carbon build up, fuel nozzle clogs, and filter blockages. Never attempt repairs or adjustments while the unit is in operation, and always follow local regulations and the manufacturer's safety guidelines.
- ✗ **DO NOT** use the heater in closed rooms, living areas, basements or below ground level.
- ✗ **DO NOT** allow untrained persons to operate the heater and **DO NOT** operate the heater without the safety guard.
- ✗ **DO NOT** move or handle the heater when hot, without wearing protective gloves. Never move the heater whilst it is operating.
- ✗ **DO NOT** leave the heater unattended for prolonged periods of time when in use. Switch the heater off and unplug from the mains before leaving work area.
- ✗ **DO NOT** fill the fuel tank whilst the heater is running or still hot. **DO NOT** over-fill the fuel container. Wipe up any spilt fuel immediately.
- ✗ **DO NOT** obstruct the air inlet (rear) and air outlet (front) of the heater and **DO NOT** use duct work in front or at the rear of the heater.
- ✗ **DO NOT** allow children or animals near the heater when in use, or whilst still hot.

- ❑ **WARNING! RISK OF ELECTRIC SHOCK. DO NOT** expose the heater to water spray, rain, dripping water or wind.
- ✖ **DO NOT** operate the heater when you are tired or under the influence of alcohol, drugs or intoxicating medication.
- ✖ **DO NOT** touch the heater outlet or cone when in use, or for a period of time after it's switched off, as these are VERY hot and will take time to cool down.
- ✖ **DO NOT** switch the heater off by disconnecting it from the mains. ALWAYS set the switch on the burner to the 'OFF' position and allow the cooling cycle to finish, before disconnecting from the mains.
- ✖ **DO NOT** use an external fuel tank. Only use the tank that is fitted to the heater, and only fill it when the heater has cooled down.
- ✖ **DO NOT** use "old" or "second-hand" diesel or anything other than clean, fresh, new diesel.
- ❑ **WARNING! A qualified installer is required to install, adjust and, where necessary, convert the appliance for use with other fuel types.**
- ✖ **DO NOT** use low-quality diesel. Always use high-quality and clean fuel that has been filtered before use. Using any other type of fuel will invalidate the warranty and could cause an explosion, a fire or the unit to malfunction.
- ✓ Ensure that the heater is correctly turned off.
- ✓ When not in use for an extended period, store in a safe, dry area, out of reach of children.
- IMPORTANT:** This appliance is not intended for persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety. Children should be supervised to ensure that they **DO NOT** play with the appliance.
- ✓ Only suitable for clean, fresh, filtered diesel.
- ✓ Cleaning and user maintenance on the appliance shall not be made by children without supervision.
- NOTE:** There should be no combustible objects within 2 metres in front of the heater, within 1.5 metres of the top, and no combustible objects or shielding objects within 0.5 metres to the left, right and rear side.
- ✓ That the appliance shall be disconnected from its power source during service and when replacing parts and, if that the removal of the plug is foreseen, it shall be clearly indicated that the removal of the plug has to be such that an operator can check from any of the points to which he has access that the plug remains removed.


2. INTRODUCTION

Versatile and compact diesel-fuelled Infrared technology heater has no electric fan, meaning there is no air movement and the heat is spread evenly in all directions, quietly and dust-free. Ideal for use in well-ventilated indoor areas including garages, workshops, warehouses and marquees. Extremely inexpensive to run, using only around 2.7L of fuel per hour. Clean burn and precisely controlled fuel supply, ensure that no unpleasant odours or carbon monoxide enter the air. Equipped with advanced safety features including overheat protection, auto-misfire, tilt, shock, low fuel shut-off sensors and flame-out fuel cut. Features 24hr timer and temperature control thermostat. Soft-touch control panel with LED display. Fitted with four castor wheels for easy manoeuvrability. Stainless exhaust available - IREX1 (End Pipe), IREX2 (1m Extension), IREX3 (90° Bend). Only suitable for use with fresh, clean diesel. The use of any other fuels or old/second-hand diesel will invalidate the warranty and may cause the unit to malfunction.

3. SPECIFICATION

Model:	IR13.V3	IR16.V3	IR19.V2	IR29
Automatic Shut Off	Yes	Yes	Yes	Yes
Fuel Tank	50L	50L	70L	70L
Fuel	Diesel	Diesel	Diesel	Diesel
Fuse Rating	13A	13A	3A	3A
Heated Area	11,477ft ³ (325m ³)	14,125ft ³ (400m ³)	14,740ft ³ (450m ³)	26,486ft ³ (750m ³)
Motor Power	80W	80W	80W	80W
Weight	46kg	50kg	57kg	87kg
Heat Output	44,500btu/hr(13kW)	55,000btu/hr(16kW)	64,000btu/hr(19kW)	99,000btu/hr(29kW)
Plug Type	3-Pin	3-Pin	3-Pin	3-Pin
Power Supply Cable Length	1.8m	1.8m	1.8m	1.8m
Running Time per Filling (Maximum)	52hr	42hr	36hr	25hr
Supply	230V~50Hz	230V~50Hz	230V~50Hz	230V~50Hz
Transport Wheels	Yes	Yes	Yes	Yes
Power:	80W	80W	80W	80W
Noise Level	58d(B)A	58d(B)A	58d(B)A	58dB(A)
Energy Efficiency Class	A	A	A	A
Nominal Heat Output:	13kW	16kW	20kW	99,000btu/hr
Energy Efficiency Index	91%	92%	92%	87.10%
Useful Energy Efficiency at Nominal Heat Output (nominal):	91%	92%	88.85%	86,229btu/hr

4. CONTROLS



ITEM	DESCRIPTION
1	LED Display for Current Temp/Set Temp-Time
2	Temperature Control Mode On
3	Cycle Time Control Mode On
4	(IR Receiver NOT FITTED TO THIS MODEL)
5	ON/OFF
6	Temp / Cycle Time Selection
7	Increase/Decrease Temp or Cycle Time Setting
8	Lock Settings - press to lock, press to unlock
9	Timer ON/OFF
10	Timer ON Indicator
11	Misfire Indicator
12	Operating Indicator
13	Fuel Gauge Display
14	Overheating Indicator
15	Tilt Indicator
16	Low/Empty fuel Indicator
17	Lock State Indicator

5. OPERATION

5.1. Connect the unit to the power supply and turn it on.

5.1.1. The LED displays the current ambient temperature.

5.2. TEMPERATURE CONTROL

NOTE: Temperature is displayed in degrees centigrade. To change to Fahrenheit hold both UP and DOWN arrows for 5 seconds.

5.2.1. Switch the unit on (fig.1.5).  The heater will start up using the last entered values of temperature and time. The unit can be Switched off by pressing the ON/OFF button again (fig.1.5). 

5.2.2. To set the required temperature, use the UP and DOWN arrows (fig.1.7). The temperature setting range is from 0°C to 40°C.

NOTE: If the set temperature is 2°C higher than current ambient temperature the unit will start working. If set temperature is 1°C below current ambient temperature, the unit will stop working.

5.3. CYCLE TIME CONTROL

5.3.1. Switch the unit on (fig.1.5).  The heater will start up using the last entered values of temperature and time. The unit can be Switched off by pressing the ON/OFF button again (fig.1.5). 

5.3.2. Press Temp/Time selector (fig.1.6 ) and wait a few seconds until Cycle Timer ON indicator (fig.1.3 ) is illuminated.

5.3.3. To set ON cycle time period, use the UP and DOWN arrows (fig.1.7). Once set to the required value, stop pressing buttons and after 3 seconds the displayed value will be set.

5.3.4. The cycle time ON value can be set from 5 minutes up to 55 minutes.

NOTE: If the input value exceeds 55 minutes, the unit will operate in continuous mode and displays



5.4. TIMER

5.4.1. To run for a set time, select the TIMER function (fig.1.9 ) and use the UP and DOWN arrows (fig.1.7) to set time. The Timer ON indicator (fig.1.10 ) will illuminate.

5.4.2. Long press the timer button (fig.1.8 ) for 3 seconds to turn off the timer.

5.5. CHILD LOCK

5.5.1. Press the child lock button (fig.1.7 ) for 3 seconds to turn on or turn off the child lock function.

NOTE: There should be no combustible objects within 2 metres in front of the heater, within 1.5 metres of the top, and no combustible objects or shielding objects within 0.5 metres to the left, right and rear side.

6. MAINTENANCE

- ❑ **WARNING!** Unplug unit from mains power supply ensure heater is cold before opening or servicing heater.
- ❑ **WARNING! DO NOT** tamper with the unit, have an experienced service engineer make any necessary adjustment or repairs.

6.1. LONG TERM STORAGE

- 6.1.1. Unscrew the fuel cap.
- 6.1.2. Using an approved siphon, remove the diesel.
- 6.1.3. Using a small amount of diesel, rinse and swirl the fuel inside the fuel tank.
- 6.1.4. Empty the tank completely.

NOTE: never mix water with fuel, it will cause rust inside the tank.

IMPORTANT: Never store leftover fuel between seasons, using old fuel can damage heater.

- 6.1.5. Store Heater in a dry, well ventilated area. Be sure that the storage area is free of dust and corrosive vapours. Repack the heater in the original packaging and keep user's manual in an easily accessible place.

6.2. FUEL / FUEL TANK

- 6.2.1. Flush tank every 200 hours of operation or as needed. **DO NOT** flush with water, use fresh paraffin (to flush NOT to fuel) only.
 - ✓ Only suitable for clean, fresh, filtered diesel.
 - ✗ **DO NOT** use "old" or "second-hand" diesel or anything other than clean, fresh, new diesel.
 - ✗ **DO NOT** use low-quality diesel. Always use high-quality and clean fuel that has been filtered before use. Using any other type of fuel will invalidate the warranty and could cause an explosion, a fire or the unit to malfunction.

6.3. NOZZLES



- 6.3.1. Nozzles should be cleaned or replaced at least once per heating season. Contaminated fuel could make this necessary immediately.
- 6.3.2. To clean dirt from nozzle, blow compressed air through nozzle front. It may be necessary to soak nozzle in clean paraffin or diesel to help loosen any particles.

6.4. FLAME SENSOR (fig.2)

- 6.4.1. The photocell should be cleaned at least once per heating season or more depending on conditions, use a cotton swab and water or alcohol to clean the lens of the photocell. Ensure the sensor is fully engaged when replacing it (fig.2).

6.5. FILTERS

- 6.5.1. The fuel filter and oil filter should be cleaned at least twice per heating season by rinsing it in clean paraffin or diesel. Contaminated or old fuel could make cleaning necessary immediately.



6.6. OIL DRAINAGE SYSTEM

Before long-distance transportation or long-term storage of the product, please drain the oil tank.

There are two modes available: Automatic and Manual.


Automatic Mode:

1. Pull out the return valve's connecting oil pipe (see fig.3) and replace it with the long oil pipe provided. Then, return the oil container to its original position.
2. Power on the product and ensure it is in standby mode. Press the 'TEMP TIME' button three times to connect, then press 'TIMER' three more times. The display will show "ODS", indicating that the oil discharge system program has started.
3. Tilt the product and repeat step 2. Try to drain the fuel tank as much as possible. When the oil pump begins to make a loud noise, it indicates that the oil has been fully drained.

NOTE: Press the  button to exit ODS mode.

Manual Mode:

1. Remove the fuel tank cap.
2. Use a screwdriver to take out the oil filter screen.
3. Use the external oil pump to drain the oil. This method allows for quick and effective emptying of the fuel tank.



6.7. PREVENTATIVE MAINTENANCE MEASURES TO BE OBSERVED


For industrial infrared diesel heaters includes regularly cleaning the burner and fuel nozzle to prevent blockages, replacing air and fuel filters according to the manufacturer's schedule, and inspecting fuel lines and connections for leaks or damage. It's important to keep the heater's exterior and ventilation areas free from dust and debris to ensure proper airflow. Safety features such as flame sensors and tip-over switches should be tested frequently to confirm they are working properly. Using clean, high-quality diesel fuel helps reduce residue build up and maintain efficient operation. Routine inspections before and after heavy use help extend the heater's lifespan and maintain safe performance.

6.8. DISASSEMBLY, RECYCLING, AND DISPOSAL

At the end of its life, the heater must be fully powered down and cooled before disassembly. Drain any remaining diesel fuel and dispose of it at an approved hazardous waste site. Recycle metal parts through a certified scrap facility, and dispose of electrical components as electronic waste in accordance with local regulations. Always follow local environmental and safety guidelines.


6.9. INSTALL EXHAUST MUFFLER (for IR29)

To install the Exhaust Muffler (IR29): Located packaged and secured inside the door on the right hand side, refer to fig.3. First remove it from the packaging and take off the protective bag. Insert the muffler into the smoke pipe fixing seat and rotate it until it is in the correct position. Align the muffler's installation hole with the hole on the fixing seat, then use a Phillips screwdriver to insert and tighten the fixing screw securely, as shown in the fig.4.



6.10. HOW TO FILL UP WITH FUEL (for IR29)


To fill up with fuel for the IR29, rotate the fuel filler cap card clockwise or counterclockwise by hand to release the fuel filler cap cover, then pull the cover outward until the fuel filler cap is visible. Align the funnel with the fuel filler cap and carefully add clean diesel fuel. Stop refuelling once the fuel level becomes visible, as this indicates the tank is full. After filling, push the fuel filler cap cover inward and rotate the upper card to the correct position to securely lock the cover. Fig.5



7. TROUBLESHOOTING

Error Code	Cause	Solution
Er01	Temperature sensor open or error.	Re-tighten connections.
Er02	Tipping over beyond 15°	Disconnect power supply and adjust levels.
Er04	Fire sensor connection.	Re-tighten connections.
Er05 and Misfire light	Air in fuel line.	Restart.
	No fuel.	Check fuel levels. Fill with clean, fresh, filtered diesel as per instructions.
	Filter clogged.	Clean / change filter.
	Motor failure.	Return to Supplier for Service.
	Igniter failing.	
	Pump failure.	
Er06	Temperature overheating.	Check unit is not covered.
Er09	Oil level sensor fault.	Re-tighten connections.
Overheating	Set temperature is below ambient.	Adjust temperature setting.

7.1. ELECTRICAL DIAGRAM



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



REGISTER YOUR PURCHASE HERE



WEEE REGULATIONS

Dispose of this product at the end of its working life in compliance with the EU Directive on Waste Electrical and Electronic Equipment (WEEE). When the product is no longer required, it must be disposed of in an environmentally protective way. Contact your local solid waste authority for recycling information.

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Please note that other versions of this product are available. If you require documentation for alternative versions, please email or call our technical team on technical@sealey.co.uk or 01284 757505.

IMPORTANT: No Liability is accepted for incorrect use of this product.

WARRANTY: Guarantee is 36 months from purchase date, proof of which is required for any claim.

Jack Sealey Ltd t/a Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk, IP32 7AR UK
Jack Sealey (EU) Ltd t/a Sealey Group, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland
Tel: 01284 757500 • **Email:** sales@sealey.co.uk • **Web:** www.sealey.co.uk

Product Information Sheet. Local Space Heaters, Gas / Liquid Fuel.

SUPPLIER_NAME_OR_TRADEMARK

Sealey EU Ltd.

DELEGATED_ACT

2024/1103/EU

MODEL_IDENTIFIER

IR13

Industrial Infrared Diesel Heater 13kW

ADDRESS

Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland

PHONE_NUMBER

01284 757 500

EMAIL_ADDRESS

TechnicalCompliance@sealey.co.uk

Indirect heating functionality	No	Direct heat output (kW)	13.0
Fuel type	Liquid	Indirect heat output (kW)	NA
Specify	diesel / kerosene	Space Heating Emissions mg/kWh	97.0

Heat output

Useful efficiency

Nominal heat output kW	13.0	at nominal heat output	86.5
Minimum heat output (indicative) kW	NA	at minimum heat output	NA
		Seasonal space heating efficiency	77.9

Auxiliary electricity consumption

Type of heat output/room temperature control

At nominal heat output kW	0.1	Single stage heat output, no room temperature control	No
At minimum heat output kW	NA	Two or more manual stages, no room temperature control	No
In standby mode kW	1.03	With mechanical thermostat room temperature control	No
		With electronic room temperature control	Yes
		With electronic room temperature control plus day timer	Yes
		With electronic room temperature control plus week timer	No
		Other control options	
		Room temperature control, with presence detection	No
		Room temperature control, with open window detection	No
		With distance control option	Yes
		With adaptive start control	No
		With working time limitation	No
		With black bulb sensor	No
		With Control accuracy	No

Permanent pilot flame power requirement

Pilot flame power requirement (if applicable) kW	NA
--	----

Suppliers website <https://www.sealey.co.uk/>

Product Information Sheet. Local Space Heaters, Gas / Liquid Fuel.

SUPPLIER_NAME_OR_TRADEMARK

Sealey EU Ltd.

DELEGATED_ACT

2024/1103/EU

MODEL_IDENTIFIER

IR16

Industrial Infrared Diesel Heater 16kW

ADDRESS

Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland

PHONE_NUMBER

01284 757 500

EMAIL_ADDRESS

TechnicalCompliance@sealey.co.uk

Indirect heating functionality	No	Direct heat output (kW)	16.0
Fuel type	Liquid	Indirect heat output (kW)	NA
Specify	diesel / kerosene	Space Heating Emissions mg/kWh	104.0

Heat output

Useful efficiency

Nominal heat output kW	16.0	at nominal heat output	86.8
Minimum heat output (indicative) kW	NA	at minimum heat output	NA
		Seasonal space heating efficiency	78.1

Auxiliary electricity consumption

Type of heat output/room temperature control

At nominal heat output kW	0.1	Single stage heat output, no room temperature control	No
At minimum heat output kW	NA	Two or more manual stages, no room temperature control	No
In standby mode kW	1.03	With mechanical thermostat room temperature control	No
		With electronic room temperature control	Yes
		With electronic room temperature control plus day timer	Yes
		With electronic room temperature control plus week timer	No
		Other control options	
		Room temperature control, with presence detection	No
		Room temperature control, with open window detection	No
		With distance control option	Yes
		With adaptive start control	No
		With working time limitation	No
		With black bulb sensor	No
		With Control accuracy	No

Permanent pilot flame power requirement

Pilot flame power requirement (if applicable) kW	NA
--	----

Suppliers website <https://www.sealey.co.uk/>

Product Information Sheet. Local Space Heaters, Gas / Liquid Fuel.

SUPPLIER_NAME_OR_TRADEMARK

Sealey EU Ltd.

DELEGATED_ACT

2024/1103/EU

MODEL_IDENTIFIER

IR19

Industrial Infrared Diesel Heater 19kW

ADDRESS

Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland

PHONE_NUMBER

01284 757 500

EMAIL_ADDRESS

TechnicalCompliance@sealey.co.uk

Indirect heating functionality	No	Direct heat output (kW)	20.0
Fuel type	Liquid	Indirect heat output (kW)	NA
Specify	diesel / kerosene	Space Heating Emissions mg/kWh	82.0

Heat output

Useful efficiency

Nominal heat output kW	20.0	at nominal heat output	88.9
Minimum heat output (indicative) kW	NA	at minimum heat output	NA
		Seasonal space heating efficiency	80.0

Auxiliary electricity consumption

Type of heat output/room temperature control

At nominal heat output kW	0.1	Single stage heat output, no room temperature control	No
At minimum heat output kW	NA	Two or more manual stages, no room temperature control	No
In standby mode kW	1.03	With mechanical thermostat room temperature control	No
		With electronic room temperature control	Yes
		With electronic room temperature control plus day timer	Yes
		With electronic room temperature control plus week timer	No
		Other control options	
		Room temperature control, with presence detection	No
		Room temperature control, with open window detection	No
		With distance control option	Yes
		With adaptive start control	No
		With working time limitation	No
		With black bulb sensor	No
		With Control accuracy	No

Permanent pilot flame power requirement

Pilot flame power requirement (if applicable) kW	NA
--	----

Suppliers website

<https://www.sealey.co.uk/>

Product Information Sheet. Local Space Heaters, Gas / Liquid Fuel.

SUPPLIER_NAME_OR_TRADEMARK

Sealey EU Ltd.

DELEGATED_ACT

2024/1103/EU

MODEL_IDENTIFIER

IR29

Industrial Infrared Diesel Heater 29kW

ADDRESS

Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland

PHONE_NUMBER

01284 757 500

EMAIL_ADDRESS

TechnicalCompliance@sealey.co.uk

Indirect heating functionality	No	Direct heat output (kW)	29.0
Fuel type	Liquid	Indirect heat output (kW)	NA
Specify	Diesel	Space Heating Emissions mg/kWh	87.0

Heat output

Useful efficiency

Nominal heat output kW	29.0	at nominal heat output	91.8
Minimum heat output (indicative) kW	NA	at minimum heat output	NA
		Seasonal space heating efficiency	82.6

Auxiliary electricity consumption

Type of heat output/room temperature control

At nominal heat output kW	0.100	Single stage heat output, no room temperature control	No
At minimum heat output kW	NA	Two or more manual stages, no room temperature control	No
In standby mode kW	1.030	With mechanical thermostat room temperature control	No
		With electronic room temperature control	Yes
		With electronic room temperature control plus day timer	Yes
		With electronic room temperature control plus week timer	No
		Other control options	
		Room temperature control, with presence detection	No
		Room temperature control, with open window detection	No
		With distance control option	No
		With adaptive start control	Yes
		With working time limitation	No
		With black bulb sensor	No
		With Control accuracy	No

Permanent pilot flame power requirement

Pilot flame power requirement (if applicable) kW	NA
--	----

Suppliers website <https://www.sealey.co.uk/>